

BUILT TO LAST.



OVERVIEW

Dymax Heavy Duty Rock and Root Rakes for Track Dozers provide years of productive use.

Comprised of high tensile steel construction and featuring heavy duty shanks, these rakes are available in a variety of widths and tine spacing to meet your application requirements. Bottom Shanks are available with replacement tips and shank protection if specified.

Made for track dozers / crawler tractors. Available for most makes and models of machines up to 600 horsepower.

BRACKETS

Made to fit outside mounted push arms on Dozers. Not provided with connector blocks, pins, retainers for attaching to the push arms





DYMAXINC | Toll Free: 800.530.5407 (USA/CAN)
402 Miller Drive | Office: +1.785.456.2081
Wamego, KS 66547 USA | Fax: +1.785.456.8328

www.DYMAXINC.com sales@DYMAXINC.com

FEATURES

- For track dozers / crawler tractors.
- Heavy duty high tensile steel shanks with optional replaceable tine tips.
- Available in a variety of widths and tine spacing; call Dymax to specify dimensions for your application.
- Available for machines up to 600 horsepower.



Model #	Description	Weight lb
DX-RK-RR-136in-TD-10	Rake – Rock & Root – 136 inches wide – Track Dozer – Class 10 2.00" tine thickness x 13 tines total (Avg 10" spacing)	5,300
DX-RK-RR-156in-TD-20	Rake – Rock & Root – 156 inches wide – Track Dozer – Class 20 2.00" tine thickness x 13 tines total (Avg 10" spacing)	6,400
DX-RK-RR-158in-TD-30	Rake – Rock & Root – 158 inches wide – Track Dozer – Class 30 2.50" tine thickness x 16 tines tot (Avg 10" spacing)	8,400
DX-RK-RR-180in-TD-40	Rake – Rock & Root – 180 inches wide – Track Dozer – Class 40 3.00" tine thickness x 15 tines total	13,400

Specifications are subject to change without notice.



Wamego, KS 66547 USA | Fax: +1.785.456.8328

DYMAXINC | Toll Free: 800.530.5407 (USA/CAN) 402 Miller Drive | Office: +1.785.456.2081

www.DYMAXINC.com sales@DYMAXINC.com