



LOAD, CARRY, LIFT AND PUSH.
PUSHING PERFORMANCE.

OVERVIEW

DYMAX Pushout Buckets for Wheel Loaders, Toolcarriers and Telehandlers are the new way to handle light materials that require high dump heights and aid operators in reducing feeding overages.

Push out style buckets feature a hydraulically-driven ram that ejects the material from the bucket, avoiding the dump cycle of standard buckets and the hard-to-control rollout cycle of rollout buckets. They reduce loader lift arm fatigue and eliminate bucket fatigue associated with rollout buckets.

The highly controllable pushout bucket ram enables operators to meter material, thereby eliminating waste and spillage that occurs with rollout buckets and traditional loader buckets.



CLEAN SWEEP GAURANTEE

- Pioneered by DYMAX the interior sealed gate provides the cleanest sweep each and every time and longer lasting durability.

SIZES AVAILABLE

- 1.75-11.00yd³, 96-168in wide each model is sized to match your loaders performance.

WEAR PROTECTION

- Replaceable bolt on cutting edges; standard 1x10 heat treated edge group with countersunk nylon plugs. Includes bolt on rear wear pads.



FASTER LOADING TIMES

Operators claim that loading trucks is faster with **DYMAX Pushout Buckets**. Operators only have to operate the auxiliary hydraulic circuit to dump. This eliminates the need for rapidly shaking the bucket, which takes extra time to unload materials.

Faster loading times improve speed and efficiency to help reduce fuel consumption, lowering overhead and operationsl costs.



Model Code	Description	Wheel Loader	HP Range	Weight (lbs)
DX-BK-PO-2.69cyd-WL-30	Bucket-Push-Out-2.69 cyd capacity-Wheel Loader-Class 30	Wheel Loader or Telehandler	75-100	2,000
DX-BK-PO-2.79cyd-WL-40	Bucket-Push-Out-2.79 cyd capacity-Wheel Loader-Class 40	Wheel Loader or Telehandler	125-150	4,000
DX-BK-PO-3.61cyd-WL-50	Bucket-Push-Out-3.61 cyd capacity-Wheel Loader-Class 50	Wheel Loader	125-150	4,400
DX-BK-PO-4.52cyd-WL-50	Bucket-Push-Out-4.52 cyd capacity-Wheel Loader-Class 50	Wheel Loader	125-150	5,000
DX-BK-PO-5.10cyd-WL-60	Bucket-Push-Out-5.10 cyd capacity-Wheel Loader-Class 60	Wheel Loader	170-200	6,100
DX-BK-PO-5.50cyd-WL-60	Bucket-Push-Out-5.50 cyd capacity-Wheel Loader - Class 60	Wheel Loader	170-200	5,800
DX-BK-PO-5.92cyd-WL-60	Bucket-Push-Out-5.92 cyd capacity-Wheel Loader-Class 60	Wheel Loader	170-200	6,050
DX-BK-PO-6.50cyd-WL-70	Bucket-Push-Out-6.50 cyd capacity-Wheel Loader - Class 70	Wheel Loader	210-250	6,350
DX-BK-PO-7.03cyd-WL-70	Bucket-Push-Out-7.03 cyd capacity-Wheel Loader-Class 70	Wheel Loader	210-250	6,600
DX-BK-PO-7.56cyd-WL-70	Bucket-Push-Out-7.56 cyd capacity-Wheel Loader-Class 70	Wheel Loader	210-250	6,100
DX-BK-PO-7.81cyd-WL-70	Bucket-Push-Out-7.81 cyd-Wheel Loader-Class 70	Wheel Loader	210-250	7,650
DX-BK-PO-9.06cyd-WL-80	Bucket-Push-Out-9.06 cyd capacity-Wheel Loader-Class 80	Wheel Loader	260-300	8,500

Design and specifications are subject to change without notice. Rev 2021.07



DYMAXINC
 402 Miller Drive
 Wamego, KS 66547 USA

Toll Free: 800.530.5407 (USA/CAN)
 Office: +1.785.456.2081
 Fax: +1.785.456.8328

www.DYMAXINC.com
sales@DYMAXINC.com