

SAND AND GRAVEL BUCKETS



OVERVIEW

Dymax Sand and Gravel Buckets are designed for use in abrasive materials or extreme wear applications, such as loading sand and gravel or charging asphalt plants.

Buckets incorporate proven design criteria, which yield superior loading characteristics over many general purpose buckets. Dymax Sand and Gravel Buckets feature specialized wear plates on the sides and bottom of the bucket.

High tensile wear-resistant steel is used throughout for greater durability, increased strength and abrasion resistance.



Convex Sidecutters

Provide increased material retention per load.

FEATURES AND SPECIFICATIONS

- Sand and Gravel Bucket design increases capacity by 15% compared to standard bucket models, without affecting the machine stability.
- Convex side bars allow operators to retain more material.
- Specially designed spill plate retains the load and directs material away from the pins.
- Wear plates protect the integrity of the floor and sides of the bucket.
- Straight or Spade nose available.
- Available in direct pin-on models, or with hooks installed to work with the Dymax coupler system or other popular couplers.

Spill Plate

Helps keep sand and materials away from lift arms.



Options

Spade nose edge, specialized liner system such as Hardox and carbide overlay.

Model #	Description	Weight lb
DX-BK-SG-10.00cyd-WL-100	Bucket-Sand & Gravel-10.00 cyd capacity-Wheel Loader-Class 100	10,400
DX-BK-SG-11.00cyd-WL-100	Bucket-Sand & Gravel-11.00 cyd capacity-Wheel Loader-Class 100	10,800
DX-BK-SG-3.50cyd-WL-50	Bucket-Sand & Gravel-3.50 cyd capacity-Wheel Loader-Class 50	3,400
DX-BK-SG-3.50cyd-WL-60	Bucket-Sand & Gravel-3.50 cyd capacity-Wheel Loader-Class 60	3,850
DX-BK-SG-4.75cyd-WL-70	Bucket-Sand & Gravel-4.75 cyd capacity-Wheel Loader-Class 70	4,750
DX-BK-SG-5.75cyd-WL-80	Bucket-Sand & Gravel-5.75 cyd capacity-Wheel Loader-Class 80	5,500
DX-BK-SG-6.00cyd-WL-80	Bucket-Sand & Gravel-6.00 cyd capacity-Wheel Loader-Class 80	5800,
DX-BK-SG-7.50cyd-WL-90	Bucket-Sand & Gravel-7.50 cyd capacity-Wheel Loader-Class 90	7,850
DX-BK-SG-7.80cyd-WL-90	Bucket-Sand & Gravel-7.80 cyd capacity-Wheel Loader-Class 90	7,500
DX-BK-SG-8.00cyd-WL-90	Bucket-Sand & Gravel-8.00 cyd capacity-Wheel Loader-Class 90	9,450
DX-BK-SG-9.00cyd-WL-90	Bucket-Sand & Gravel-9.00 cyd capacity-Wheel Loader-Class 90	9,500
DX-BK-SGAR-9.60cyd-WL-90	Bucket-Sand & Gravel Abrasion Resistant-9.60 cubic yard capacity-Wheel Loader-Class 90	11,450
DX-BK-SGSPD-11.00cyd-WL-100	Bucket-Sand & Gravel Spade Nose-11.00 cyd capacity-Wheel Loader-Class 100	11,800
DX-BK-SGSPD-11.50cyd-WL-100	Bucket-Sand & Gravel Spade Nose-11.50 cyd capacity-Wheel Loader-Class 100	11,950
DX-BK-SGSPD-12.00cyd-WL-100	Bucket-Sand & Gravel Spade Nose-12.00 cyd capacity-Wheel Loader-Class 100	12,500

Specifications are subject to change without notice.



DYMAXINC | Toll Free: 800.530.5407 (USA/CAN)
 402 Miller Drive | Office: +1.785.456.2081
 Wamego, KS 66547 USA | Fax: +1.785.456.8328

www.DYMAXINC.com
sales@DYMAXINC.com