

BUILT TO LAST.



OVERVIEW

Fits:	Gradall excavators
Rotation:	360° continuous
Tilt:	None
Hydraulics:	Requires only 1 auxiliary circuit
Coupler Lock:	Hydraulic or Manual
Functions:	1 or 2 circuits (5 lines) below,
	subject to coupler lock
Installation:	Wire cable kit + drain & jump lines

What it is?

The Dymax Rotating Coupler adds full 360° rotation to Gradall Excavators, working seamlessly with the machine's built-in 220° boom tilt. No tilt is required in the coupler itself, so you can get more done with fewer adjustments.

APPLICATIONS

- Railway Maintenance Handle tools and attachments on or off track.
- Municipal and Utility work Ideal for mowing, ditch cleaning, and roadside work.
- Forestry and Land Clearing Rotate grapples and tree shears with precision.
- **General Construction** Grading, trenching or material handling tasks.
- Demolition Superior access in confined spaces.

KEY BENEFITS

- 360° continuous rotation.
- Uses factory auxiliary hydraulics.
- Custom Dymax valve for secure locking and proportional control.
- No tilt needed Gradall handles that.
- Simple bolt-on toolbar attachments for odd jobs.



 DYMAXINC
 Toll Free: 800.530.5407 (USA/CAN)

 402 Miller Drive
 Office: +1.785.456.2081

 Wamego, KS 66547 USA
 Fax: +1.785.456.8328

www.DYMAXINC.com sales@DYMAXINC.com



Model Code / Group No. Description	Rotation Degrees	Weight (lbs)	
DX-QC-PGH-360GRADALL-HX-14/18T ; 7210D2 Quick Coupler-Pin Grab Hydraulic-360 rotator Gradall compatible	360	1,470	
STANDARD FEATURES:			
Full 360° continuous rotation system • Hydraulic camlock pin grab coupler compatible with Gradall standard attachments • Proportional multifunction control valve with control group • Toolbar interface <i>(toolbar attachments sold separately)</i>			
INSTALLATION REQUIREMENTS:			
Dealer to install control group from coupler to cab.			
Options: Manual locking coupler, Cat A Link (65MM) compatible			
Toolbar Attachments: Ballast rake, ballast blade, lift hook			

Design and specifications are subject to change without notice.



Toolbar Attachment Shown with ballast clearing blade installed



Integrated Technology Proportional control of multiple functions using factory auxiliary hydraulics.



 DYMAXINC
 Toll Free: 800.530.5407 (USA/CAN)

 402 Miller Drive
 Office: +1.785.456.2081

 Wamego, KS 66547 USA
 Fax: +1.785.456.8328

www.DYMAXINC.com sales@DYMAXINC.com